

PERFORMANCE DATA

Unit Size (in.)	Inlet Size (in.)	Air Flow (cfm)	Filter	Static Pressure (in. w.g.)	Sound (NC)
24 x 24	10	100	HEPA 99.99% .3 µm	0.22	-
		150		0.31	-
		200		0.41	-
		250		0.50	-
		100	ULPA 99.9995% .12 µm	0.30	-
		150		0.45	-
		200		0.61	-
		250		0.76	-
24 x 36	10	150	HEPA 99.99% .3 µm	0.19	-
		200		0.24	15
		250		0.30	19
		300		0.36	23
		350		0.42	27
		400		0.48	30
		150	ULPA 99.9995% .12 µm	0.30	-
		200		0.38	15
		250		0.45	19
		300		0.56	23
		350		0.67	27
		400		0.75	30
24 x 48	12	200	HEPA 99.99% .3 µm	0.16	-
		300		0.25	-
		400		0.33	-
		500		0.41	17
		600		0.50	23
		200		ULPA 99.9995% .12 µm	0.27
		300	0.39		-
		400	0.50		-
		500	0.63		17
		600	0.74		23

Performance Notes:

1. sp = Static Pressure, in. w.g.
2. cfm = Air flow in cubic feet per minute, cfm.
3. NC = Noise Criteria. NC values are based on room absorption of 10dB re 10⁻¹² watts.
4. Blanks "-" indicate an NC level below 15.
5. sp and NC at full open damper position.
6. Tested in accordance with ASHRAE Standard 70-2006.