

## **PDMC - Perforated Diffuser with Rotatable Modular Cores**







#### **CONSTRUCTION:**

- $\bullet$  Perforated face  $^{3/}$ 16" (5mm) holes, 51% free area:
  - ☐ F-ST Steel face
  - ☐ F-AL Aluminum face
- Frame and backpan steel construction
- Pattern deflectors aluminum
- · Steel spring latches

#### FINISH:

- · Perforated face
- ☐ B12 Standard White
- Backpan and outer frame
  - ☐ B12 Standard White
  - ☐ BBP Black (available with frames 3, 15 and 17B only)

#### Optional finishes available:

- Optional colors
- Custom colors
- · Armstrong coordinated finishes

See finishes brochure for additional information. Contact your PRICE representative for leadtimes and pricing.

#### **OPTIONAL STEEL DAMPERS:**

- · For round ducts:
  - ☐ VCR7 Radial opposed blade damper
  - □ VCR8 Full flow damper with duct mounting ring (n/a with 16" or 18" inlet)
  - □ VCR8E Full flow damper, diffuser neck mounted (n/a with 16" or 18" inlet)
  - □ VCR9 Radial damper (n/a with 15", 16" or 18" inlets)
- For square / rectangular ducts:
  - ☐ VCS3 Opposed blade damper

#### **OPTIONS:**

- · Insulation:
  - ☐ R6 Molded backpan insulation (available with frame A only)
  - ☐ AFI Foil backed fiberglass insulation (available with frame B only)
- Hangers:
  - ☐ Integral hanger loops (standard)
  - ☐ EHT Extended hanger tabs
- $\square$  BN Beaded round inlet neck with extended  $2^{1/2}$ " (64mm) length

## NOTES:


- Face panel is removable
- · Dampers ship loose
- Factory tolerance ±1/32" (1mm)


FRAME STYLES:


☐ 1 - Surface Mount

☐ 2 - Snap-In

 $\square$  3 -  $^{15}/_{16}$ " T-Bar Lay-In












□ 15 - <sup>15/</sup>16" Tegular T-bar

☐ 17B - 9/16" Bolt Slot T-Bar only







**Note:** Style 17B available in 12"x12" and 24"x24" ceiling modules only

ALL METRIC DIMENSIONS () ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PROJECT:

ENGINEER:

CUSTOMER:

SPEC. SYMBOL:


PDMC
PERFORATED DIFFUSER
WITH ROTATABLE
MODULAR CORES

2023-01-20



# **PDMC - Perforated Diffuser with Rotatable Modular Cores**

Cores are factory set for 4-Way pattern and can be field adjusted for other patterns, as shown:



	Round Duct								Square / Rectangular Duct							
Module Size	6" (152mm)	8" (203mm)	10" (254mm)	12" (305mm)	14" (356mm)	15" (381mm)	16" (406mm)	7 2	6" x 6" (152mm x 152mm)	8" x 8" (203mm x 203mm)	××	××	××	××	16" x 16" (406mm x 406mm)	18" x 18" (457mm x 457mm)
12" x 12"	В								В							
16" x 16"	В	В	В						В	В	В					
24" x 24"	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α
300mm x 300mm	В								В							
400mm x 400mm	В	В							В	В						
600mm x 600mm	В	В	В	В	В	В	В		В	В	В	В	В	В	В	

Letters indicate frame profile supplied for each module / inlet combination (see section details). Module / inlet size combinations with a blank are not available.

### FRAME PROFILES:





Scan for link to additional product information

PROJECT:

ENGINEER:

CUSTOMER:

SPEC. SYMBOL:

ALL METRIC DIMENSIONS ( ) ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PDMC
PERFORATED DIFFUSER
WITH ROTATABLE
MODULAR CORES