



MODEL	LENGTH	SLOTS	H	D							
				4"	5"	6"	7"	8"	10"	12"	
SDB75	24"	1	5 ⁹ / ₁₆ " (141)	•							
		2	7 ⁹ / ₁₆ " (192)			•		○	○	○	
		3	8 ⁹ / ₁₆ " (217)			•	•	○	○	○	
		4	9 ⁹ / ₁₆ " (243)			•		•	○	○	
	48"	1	6 ⁹ / ₁₆ " (167)		•	○		○	○	○	
		2	8 ⁹ / ₁₆ " (217)			•	•	○	○	○	
		3	9 ⁹ / ₁₆ " (243)			•		•	○	○	
		4	11 ⁹ / ₁₆ " (294)			•		•	•	*	
	60"	1	7 ⁹ / ₁₆ " (192)			•		○	○	○	
		2	9 ⁹ / ₁₆ " (243)			•		•	○	○	
		3	11 ⁹ / ₁₆ " (294)			•		•	•	*	
		4	11 ⁹ / ₁₆ " (294)				•		•	*	

- = AVAILABLE AS ROUND INLET
- = AVAILABLE AS 4" (102) FLAT OVAL INLET:
 6" (152) = 4" x 7" (102 x 178)
 8" (203) = 4" x 10¹/₈" (102 x 257)
 10" (254) = 4" x 13¹/₄" (102 x 337)
 12" (305) = 4" x 16³/₈" (102 x 416)
- * = AVAILABLE AS 6" (152) FLAT OVAL INLET:
 12" (305) = 6" x 15¹/₄" (152 x 387)

NOMINAL LENGTH:

- 24" (610)
- 36" (914)
- 48" (1219)
- 60" (1524)

SLOTS	W	
	SDB75	
1	1 ⁹ / ₁₆ " (40)	
2	3 ¹ / ₁₆ " (78)	
3	4 ⁹ / ₁₆ " (116)	
4	5 ¹ / ₁₆ " (129)	

MATERIAL:

- COATED STEEL

FINISH:

- MILL FINISH

INSULATION OPTIONS:

- (SELECT MODEL SDBI)
- CF - INTERNAL COATED FIBERGLASS
 - FF - INTERNAL FIBER FREE FOAM

MODELS:

- SDB(I)75 - TO FIT SDS75 / SDR75

NOTES:

- SDBI ENDCAPS ARE UNINSULATED
- ASSOCIATED SDS DIFFUSERS MUST BE SPECIFIED AND ORDERED AS SEPARATE ITEMS
- FOR USE IN TECHZONE T-BAR CEILING SYSTEMS FOR USE WITH SDS TYPES 18, 19, 20
- 4 SLOT FOR USE WITH SDS TYPES 18 AND 19 ONLY
- FACTORY TOLERANCE ± 1/32" (1)

ALL METRIC DIMENSIONS () ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PROJECT:		PRICE®	
ENGINEER:			SDB, SDBI PLENUM TYPE 18
CUSTOMER:			
SUBMITTAL DATE:	SPEC. SYMBOL:	2015/09/22	