



UNIT SIZE	INLET SIZES		WIDTH	HEIGHT		LENGTH	
	D	W		H	A	L	
4	3 7/8 (98)	12 (305)	12 (305)	8 (203)	6 3/8 (162)	35 13/16 (910)	
5	4 7/8 (124)			10 (254)			
6	5 7/8 (149)						
7	6 7/8 (175)						
8	7 7/8 (200)						
9	8 7/8 (225)	14 (356)	12 1/2 (318)	4 3/8 (111)			
10	9 7/8 (251)	20 (508)	17 1/2 (445)				
12	11 7/8 (302)	24 (610)	18 (457)				
14	13 7/8 (352)	38 (965)					
16	15 7/8 (403)						
24 x 16	23 7/8 (603) x 15 7/8 (403)		38 (965)	18 (457)	3 1/2 (89)	27 1/2 (670)	

STANDARD CONSTRUCTION:

- 1" (25mm) THICK INTERNAL FIBERGLASS INSULATION WHICH MEETS REQUIREMENTS OF NFPA 90A AND UL181.
- 22 GAUGE GALVANIZED STEEL HOUSING. MECHANICALLY SEALED, LEAK RESISTANT CONSTRUCTION.
- RECTANGULAR DISCHARGE OPENING WITH SLIP AND DRIVE CLEAT DUCT CONNECTION.
- MULTI-POINT, CENTER AVERAGING AIRFLOW SENSOR.
- 1/2" (13mm) GALVANIZED DAMPER SHAFT WITH POSITION INDICATOR.
- LEFT HAND UNIT SHOWN (CLH), RIGHT HAND AVAILABLE.
- SILENCER - MEDIUM PRESSURE STYLE, 22 GAUGE GALVANIZED CASING WITH PERFORATED LINER OVER FIBERGLASS ACOUSTIC MEDIA.

CONTROLS OPTIONS:

- FIELD MOUNTED CONTROLS, SUPPLIED BY OTHERS (FLD)
- FACTORY MOUNTED DIGITAL CONTROLS, SUPPLIED BY OTHERS (FAC)

CONTROLS SUPPLIED AND MOUNTED BY PRICE (EHP):

- DIGITAL CONTROLS (DIG)
- PNEUMATIC CONTROLS (PNEU)

UNIT OPTIONS:

- NEMA1 CONTROLS ENCLOSURE (PS)
- DISCONNECT SWITCH (DSW)
- HANGER BRACKETS (HB)
- BOTTOM REMOVABLE SENSOR (RS)
- BRASS AIRFLOW SENSOR GAUGE TAPS (GT)

BOTTOM ACCESS DOOR:

- ACCESS DOOR WITH SCREWS (AD)
- ACCESS DOOR WITH SNAP LATCHES (ADL)
- ACCESS DOOR WITH QUARTER TURN LATCHES (ADQ)

LINER OPTIONS:

- FIBER FREE FOAM 1" (25mm) (FF1)
- FOIL FACED FIBERGLASS BOARD 1" (25mm) (FB1)
- SOLID METAL WITH FG1 (SM1)
- CLEANROOM ANGLES WITH FB1 (CRAF1)
- PERFORATED METAL WITH FB1 (AFPM1)

SILENCER LINER OPTIONS:

- POLYMER LINER (PL)
- FIBERGLASS CLOTH (FC)



ALL METRIC DIMENSIONS () ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PROJECT:		PRICE	SDVQ
ENGINEER:			
CUSTOMER:		274115	
SUBMITTAL DATE:	SPEC. SYMBOL:	07/04/2022	