



PCM - POWER AND CONTROL MODULE
CONTROL BY PRICE FOR INTERIOR AND PERIMETER ZONES



NOTES:

- CONTROLS UP TO 30 DAMPERS IN LARGE ZONES, 12 OF WHICH CAN BE LINEAR HEATERS
- POWER DISCONNECT SWITCH
- OVERLOAD INDICATOR LEDS
- 20 GAUGE GALV. STEEL ENCLOSURE
- CABLE INCLUDED WITH THERMOSTAT
- ETL CERTIFIED TO UL873
- CONTROL BOARDS ARE RoHS COMPLIANT
- FCC PART 15, SUBPART B COMPLIANT
- CE COMPLIANT

MODUFLEX ZONE TYPE AND SIZE:

- IZ2 - INTERIOR ZONE - UMC3 COOL
 - SMALL ZONE - COOLING (UPTO 12 DAMPERS)
 - LARGE ZONE - COOLING (UPTO 30 DAMPERS)
- PZ1 - PERIMETER ZONE WITH UMC3 HEAT AND COOL
 - SMALL ZONE - HEATING AND COOLING (UPTO 12 HEATERS AND/OR DAMPERS)
 - LARGE ZONE - HEATING AND COOLING (UPTO 12 HEATERS AND 18 DAMPERS)

HEATING TYPE (PZ1 ONLY):

- LNT
- LFH

TRANSFORMER OPTIONS:

- 115/24 VAC
- 240/24 VAC
- 277/24 VAC

THERMOSTAT CFLEX CABLE LENGTH (PURPLE):

- 15 FT
- 25 FT
- 35 FT

MODUFLEX ZONE TYPE AND SIZE:

- NO PRICE THERMOSTAT, 0-10 VDC INPUT SIGNAL BY OTHERS
- BLANK FACE THERMOSTAT
- DIAL SET-POINT THERMOSTAT
- LCD THERMOSTAT
- LCD WITH MOTION SENSOR THERMOSTAT
- LCD WITH CO2 AND HUMIDITY MONITORING THERMOSTAT
- WIRELESS WITH DIAL SET-POINT THERMOSTAT (DIFFUSER REQUIRED FOR WIRELESS RECIEVER)

HIGH VOLTAGE MODULAR CONNECTION (OPTIONAL):

- PLUG AND RECEPTACLE FACTORY-WIRE
 - HIGH VOLTAGE CONNECTION CABLES CAN BE ORDERED SEPARATELY THROUGH THE HVC MODEL






Intertek

ALL METRIC DIMENSIONS [] ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PROJECT:		price [®]	
ENGINEER:		APPROVED BY: PS	PCM POWER AND CONTROL MODULE CONTROL BY PRICE INTERIOR AND PERIMETER ZONES
CUSTOMER:		DRAWING NO: 269820	
SUBMITTAL DATE:	SPEC. SYMBOL:	DATE DRAWN: 04/17/2024	

PCM - POWER AND CONTROL MODULE

CONTROL BY OTHERS



NOTES:

- ALLOWS CONNECTING THIRD PARTY CONTROLLERS TO A DAISY CHAIN PLUG AND PLAY BOARD FOR EASY CONNECTION TO PRICE DAMPERS
- POWER DISCONNECT SWITCH
- POWER INDICATOR LEDES
- OVERLOAD INDICATOR LEDES
- 20 GAUGE GALV. STEEL ENCLOSURE
- ETL CERTIFIED TO UL873
- FCC PART 15, SUBPART B COMPLIANT
- CONTROL BOARDS ARE RoHS COMPLIANT
- CE COMPLIANT

CONTROLS OPTIONS:

- FACTORY MOUNTED DIGITAL CONTROL SUPPLIED BY OTHERS
- FIELD MOUNTED CONTROLS SUPPLIED BY OTHER

ZONE SIZE:

- SMALL ZONE - COOLING (UPTO 12 DAMPERS)
- LARGE ZONE - COOLING (UPTO 30 DAMPERS)
- SMALL ZONE - HEATING AND COOLING (UPTO 12 HEATERS AND/OR DAMPERS)
- LARGE ZONE - HEATING AND COOLING (UPTO 12 HEATERS AND 18 DAMPERS)


TRANSFORMER OPTIONS:

- 115/24 VAC
- 240/24 VAC
- 277/24 VAC


HIGH VOLTAGE MODULAR CONNECTION (OPTIONAL):

- PLUG AND RECEPTACLE FACTORY-WIRE
 - HIGH VOLTAGE CONNECTION CABLES CAN BE ORDERED SEPARATELY THROUGH THE HVC MODEL


ALL METRIC DIMENSIONS [] ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.



SMALL ZONE COOLING



LARGE ZONE COOLING





HEATING AND COOLING ZONE



Intertek

PROJECT:		price	
ENGINEER:		APPROVED BY: PS	PCM POWER AND CONTROL MODULE CONTROL BY OTHERS
CUSTOMER:		DRAWING NO: 269831	
SUBMITTAL DATE:	SPEC. SYMBOL:	DATE DRAWN: 04/17/2024	

PCM - POWER AND CONTROL MODULE
CONTROL BY PRICE FOR PLENUM PRESSURIZATION



NOTES:

- POWER DISCONNECT SWITCH
- POWER INDICATOR LED AND OVERLOAD INDICATOR LEDS ON PCU BOARD
- 20 GAUGE GALV. STEEL ENCLOSURE
- CABLE INCLUDED WITH THERMOSTAT
- CONNECT UPTO 3 PRESSURE SENSORS (RPN)
- ETL CERTIFIED TO UL873
- CONTROL BOARDS ARE RoHS COMPLIANT
- FCC PART 15, SUBPART B COMPLIANT
- CE COMPLIANT

MODUFLEX ZONE TYPE:

- PP1 - PLENUM PRESSURIZATION

ZONE SIZE:

- SMALL ZONE - COOLING (UPTO 12 DAMPERS)

PRESSURE CONTROL OPTION:

- CONSTANT PRESSURE
- VARIABLE PRESSURE

PRESSURE SENSORS/RPNS:

- 1 RPN
- 2 RPNS
- 3 RPNS

TRANSFORMER OPTIONS:

- 115/24 VAC
- 240/24 VAC
- 277/24 VAC

THERMOSTAT CFLEX CABLE LENGTH (PURPLE):

- 15 FT
- 25 FT
- 35 FT

MODUFLEX ZONE TYPE AND SIZE:

- NO PRICE THERMOSTAT, 0-10 VDC INPUT SIGNAL BY OTHERS
- BLANK FACE THERMOSTAT
- DIAL SET-POINT THERMOSTAT
- LCD THERMOSTAT
- LCD WITH MOTION SENSOR THERMOSTAT
- LCD WITH CO2 AND HUMIDITY MONITORING THERMOSTAT

HIGH VOLTAGE MODULAR CONNECTION (OPTIONAL):

- PLUG AND RECEPTACLE FACTORY-WIRE
 - HIGH VOLTAGE CONNECTION CABLES CAN BE ORDERED SEPARATELY THROUGH THE HVC MODEL




Intertek

ALL METRIC DIMENSIONS [] ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PROJECT:		price [®]	
ENGINEER:		APPROVED BY: PS	PCM POWER AND CONTROL MODULE CONTROL BY PRICE PLENUM PRESSURIZATION
CUSTOMER:		DRAWING NO: 270076	
SUBMITTAL DATE:	SPEC. SYMBOL:	DATE DRAWN: 04/17/2024	

PCM - POWER AND CONTROL MODULE

CONTROL BY PRICE FOR INTERIOR ZONE STANDALONE



NOTES:

- ALLOWS CONNECTING THIRD PARTY CONTROLLERS OR PRICE DIAL THERMOSTAT TO A DAISY CHAIN PLUG AND PLAY BOARD FOR EASY CONNECTION TO PRICE DAMPERS
- POWER DISCONNECT SWITCH
- POWER INDICATOR LED
- OVERLOAD INDICATOR LED
- 20 GAUGE GALV. STEEL ENCLOSURE
- ETL CERTIFIED TO UL873
- FCC PART 15, SUBPART B COMPLIANT
- CE COMPLIANT

MODUFLEX ZONE TYPE AND SIZE:

- NO PRICE THERMOSTAT, 0-10 VDC INPUT SIGNAL BY OTHERS
- DIAL SET-POINT THERMOSTAT

HIGH VOLTAGE MODULAR CONNECTION (OPTIONAL):

- PLUG AND RECEPTACLE FACTORY-WIRE
 - HIGH VOLTAGE CONNECTION CABLES CAN BE ORDERED SEPARATELY THROUGH THE HVC MODEL

MODUFLEX ZONE TYPE:

- IZ2 STANDALONE - INTERIOR ZONE WITH UMC1 COOL, NO BACNET

ZONE SIZE:

- SMALL ZONE - COOLING (UPTO 12 DAMPERS)

TRANSFORMER OPTIONS:

- 115/24 VAC
- 240/24 VAC
- 277/24 VAC





Intertek


ALL METRIC DIMENSIONS [] ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PROJECT:		price [®]	
ENGINEER:		APPROVED BY: PS	PCM POWER AND CONTROL MODULE CONTROL BY PRICE
CUSTOMER:		DRAWING NO: 270590	
SUBMITTAL DATE:	SPEC. SYMBOL:	DATE DRAWN: 04/17/2024	

HIGH VOLTAGE MODULAR CONNECTION



RECEPTACLE



PLUG

NOTE:


- EACH PCM UNIT COMES WITH A PLUG AND A RECEPTACLE FACTORY-WIRED




ALL METRIC DIMENSIONS [] ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PROJECT:		price [®]	
ENGINEER:		APPROVED BY: PS	PCM HIGH VOLTAGE MODULAR CONNECTION
CUSTOMER:		DRAWING NO: 270591	
SUBMITTAL DATE:	SPEC. SYMBOL:	DATE DRAWN: 04/17/2024	

HIGH VOLTAGE MODULAR CABLE



STARTER CABLE



EXTENDER CABLE

HIGH VOLTAGE MODULAR CABLES:

- STARTER CABLE, 20FT
- STARTER CABLE, 40FT
- STARTER CABLE, 60FT
- EXTENDER CABLE, 20FT
- EXTENDER CABLE, 40FT
- EXTENDER CABLE, 60FT

SUPPLY POWER:

- 115/24 VAC
- 240/24 VAC
- 277/24 VAC



ALL METRIC DIMENSIONS [] ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PROJECT:		price [®]	
ENGINEER:		APPROVED BY:	HVC HIGH VOLTAGE MODULAR CABLE
CUSTOMER:		PS	
SUBMITTAL DATE:		DRAWING NO:	
SPEC. SYMBOL:		271920	
		DATE DRAWN:	
		04/17/2024	