

Price Fan & Blower Coils

Application Guide

PRODUCT SUPPORT
204.654.5613 option 2
airmovement@priceindustries.com
For more information visit
www.priceindustries.com



	HORIZONTAL UNITS							VERTICAL UNITS	
	FCHP & FCHC	FCHE	FCHG & FCHGQ	FHPP	FHPE	BCHD	ACHU	FCVC	FCVE & FCVS
APPLICATION	Height <11"	✓	✓						
	Height <15"	✓	✓	✓			✓ (8 & 12 ONLY)		
	DOAS Latent Cooling	SPECIAL		✓	✓		✓		
	DOAS Sensible Cooling	Default to FDC-DOAS or FDCLP2-DOAS and reach out to AirMovement@PriceIndustries.com for application assistance.							
PERFORMANCE	Airflow (<600 cfm)	✓	✓	✓	✓	✓	✓		
	Airflow (600 - 1200 cfm)	✓	✓	✓	✓	✓	✓	✓	✓
	Airflow (1200 - 2400 cfm)			✓	✓	✓	✓	✓	✓
	Airflow (2400 - 4000 cfm)						✓	✓	✓
	Airflow (4000+ cfm)						✓	✓	✓
	Capacity - Low (0.5 - 4 tons)	✓	✓	✓	✓	✓	✓	✓	
	Capacity - Medium (4 - 7 tons)			✓	✓	✓	✓	✓	
	Capacity - High (7 - 12 tons)						✓	✓	✓
	Duct Static - Low (0 - 0.25")	✓	✓	✓	✓	✓			
	Duct Static - Medium (0.25 - 1")			✓	✓	✓	✓	✓	
CONFIGURATIONS	Duct Static - High (1"+)			✓		✓	✓		
	Exterior - painted		✓	SPECIAL		✓	SPECIAL	SPECIAL	
	Direct Drive Plenum Fan with EC motor							✓	
	Heating - Hot water	✓	✓	✓	✓	✓	✓	✓	✓
	Heating - Electric coil			✓					
	FAI - Damper with Airflow Measurement			✓	✓		✓	SPECIAL	
	FAI - Auto flow control	SPECIAL		SPECIAL	✓		SPECIAL		✓
	IAQ - fiber free insulation	✓	✓	✓	✓	✓	✓	✓	✓
	IAQ - solid metal liner			✓			✓	✓ (SIZE 30 ONLY)	
	IAQ - MERV 13 filters	✓	✓	✓	✓	✓	✓	✓	✓
OPTIONS	Silencer - Discharge			✓ (FCHGQ ONLY)			✓		
	Silencer - Inlet				✓		SPECIAL		
	Seismic	✓	✓	✓			✓		
	Controls - BACNET t-stat	✓	✓	✓	✓	✓	✓	✓	✓
	Controls - Factory-mounted valve package	✓ (FCHP ONLY)	✓	SPECIAL	✓	✓	✓	✓	✓
	Controls - Drain pan overflow switch	✓	✓	✓	✓	✓	✓	✓	✓